

NEW

Merit Laureate® Hydrophilic Guide Wires

May not be available
for all OEM applications.

MERIT LAUREATE STANDARD HYDROPHILIC GUIDE WIRES

Catalog Number	Description	Size	Length		# per	
			Cm	Core	Box	
LWSTDA3580	Standard/Angled Tip	.035" (0.89mm)	80	F	5	
LWSTDA35150	Standard/Angled Tip	.035" (0.89mm)	150	F	5	
LWSTDS35150	Standard/Straight Tip	.035" (0.89mm)	150	F	5	
LWSTFA3580	Stiff/Angled Tip	.035" (0.89mm)	80	F	5	
LWSTFA35150	Standard/Angled Tip	.035" (0.89mm)	150	F	5	

MERIT LAUREATE SPECIALTY HYDROPHILIC GUIDE WIRES

Catalog Number	Description	Size	Length		# per	
			Cm	Core	Box	
LWSTDA35180	Standard/Angled Tip	.035" (0.89mm)	180	F	5	
LWSTDA35260EX	Standard/Angled Tip	.035" (0.89mm)	260	F	5	Exchange
LWSTDS35180	Standard/Straight	.035" (0.89mm)	180cm	F	5	
LWSTFA35180	Stiff/Angled	.035" (0.89mm)	180cm	F	5	
LWSTFA35260EX	Stiff/Angled	.035" (0.89mm)	260cm	F	5	Exchange
LWSTFS35180	Stiff/Straight	.035" (0.89mm)	180cm	F	5	
LWSTFS35260EX	Stiff/Straight	.035" (0.89mm)	260cm	F	5	Exchange

MERIT LAUREATE SMALL DIAMETER SPECIALTY HYDROPHILIC GUIDE WIRES

Catalog Number	Description	Size	Length		# per	
			Cm	Core	Box	
LWSTDA1880	Standard/Angled	.018" (0.46mm)	80cm	F	5	
LWSTDA18150	Standard/Angled	.018" (0.46mm)	150cm	F	5	
LWSTDA18180	Standard/Angled	.018" (0.46mm)	180cm	F	5	
LWSTDA18260EX	Standard/Angled	.018" (0.46mm)	260cm	F	5	Exchange
LWSTDA25150	Standard/Angled	.025" (0.64mm)	150cm	F	5	
LWSTDA25180	Standard/Angled	.025" (0.64mm)	180cm	F	5	
LWSTDS25180	Standard/Straight	.025" (0.64mm)	180cm	F	5	
LWSTDA25260EX	Standard/Angled	.025" (0.64mm)	260cm	F	5	Exchange