

Straight Guide Wires

PTFE-Coated, Inqwire Guide Wires

Catalog Number	New Configuration Catalog Number	Description	Size	Length		Heparin # Per	
				cm	Core	Coated	Box
6676-A1		Straight	.018" (0.46mm)	150	F		10
6676-B3		Straight	.018" (0.46mm)	180	F		5
6676-C1		Straight	.021" (0.53mm)	150	F		10
6676-D3		Straight	.021" (0.53mm)	180	F		5
	IQ35F150S	Straight	.035" (0.89mm)	150	F		10
	IQH35F150S	Straight	.035" (0.89mm)	150	F	H	10
	IQ35F260S	Straight	.035" (0.89mm)	260	F		10
6690-41		Straight	.035" (0.89mm)	150	M		10
6690-71		Straight	.035" (0.89mm)	150	M	H	10
6690-61		Straight	.038" (0.97mm)	150	M		10
	IQ38F150S	Straight	.038" (0.97mm)	150	F		10
	IQ38F260S	Straight	.038" (0.97mm)	260	F		10
6646-11		Straight 7cm TC	.035" (0.89mm)	145	M		10
	IQ35F150NLT	Newton; LT (13.5cm)	.035" (0.89mm)	150	F		10
	IQH35F150NLT	Newton; LT (13.5cm)	.035" (0.89mm)	150	F	H	10
	IQ35F150NLLT	Newton; LLT (18.5cm)	.035" (0.89mm)	150	F		10
	IQH35F150NLLT	Newton; LLT (18.5cm)	.035" (0.89mm)	150	F	H	10
	IQ35F150NLLLT	Newton; LLLT(23.5cm)	.035" (0.89mm)	150	F		10
6677-B1		Newton; LLT (18.5cm) 3mm J	.035" (0.89mm)	150	F		10
	IQ35F80B	Bentson (23cm)	.035" (0.89mm)	80	F		10
	IQ35F150B	Bentson (23cm)	.035" (0.89mm)	150	F		10
8819-D1	IQH35F150B	Bentson (23cm)	.035" (0.89mm)	150	F	H	10
	IQ35F180B	Bentson (23cm)	.035" (0.89mm)	180	F		10
	IQH35F180B	Bentson (23cm)	.035" (0.89mm)	180	F	H	5
	IQ35F260B	Bentson (23cm)	.035" (0.89mm)	260	F		10
	IQ38F150B	Bentson (23cm)	.038" (0.97mm)	150	F		10
	IQH38F150B	Bentson (23cm)	.038" (0.97mm)	150	F	H	10
	IQ35F150BC	Bentson (15cm)	.035" (0.89mm)	150	F		10
	IQ35F150BST	Bentson ST (10cm)	.035" (0.89mm)	150	F		10
	IQ35F180BST	Bentson ST (10cm)	.035" (0.89mm)	180	F		10
	IQ38F150BST	Bentson ST (10cm)	.038" (0.97mm)	150	F		10
6680-61		Super Stiff	.035" (0.89mm)	80	F		10
6680-51		Super Stiff	.035" (0.89mm)	100	F		10
6680-11		Super Stiff	.035" (0.89mm)	150	F		10
6680-71		Super Stiff	.035" (0.89mm)	180	F		10
6680-23		Super Stiff	.035" (0.89mm)	260	F		5
6680-31		Super Stiff	.038" (0.97mm)	150	F		10
6680-43		Super Stiff	.038" (0.97mm)	180	F		5

All "J" tip fixed core wires are finger-straightenable. FB = Firm Body ST = Short Taper
H= Heparin Coating (R) = Rosen F=Fixed Core M= Moveable Core TC = Tapered Core
* New guide wire configurations packaged 10 per box. Original guide wires packaged 5 per box.